Claybrook.

# BIBLIOTECA

A chromatically fantastic collection of porcelain tiles in twelve tonal options, with both a plainer matt finish brick that's suitable for floor and wall, and a beautiful speckle glaze finish tile for wall. The speckle or plain can be used alone or selected together to create patterns.

**24 BASES / 12 COLOURS / 2 FINISHES / 1 FORMAT**



Biblioteca Olive Speckle



Biblioteca Claret and Frost Speckle

## PLAIN BRICK



Zest



Celadon



Sky



Olive



Herb



Frost

## SPECKLE BRICK



Zest Speckle



Celadon Speckle



Sky Speckle



Olive Speckle



Herb Speckle



Frost Speckle



Shade Variation / V2 - Slight



Slip Rating / Plain Brick - R10 A+B | PTV 36+ Shod



Requires Sealing / No



Material / Glazed Porcelain

Recycled Content / 46%

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.

1.9.26

Claybrook.

# BIBLIOTECA

## Installation and Technical Advice

PLAIN BRICK


Fig


Cream


Coffee


Sorbet


Claret


Chestnut

SPECKLE BRICK


Fig Speckle


Cream Speckle


Coffee Speckle


Sorbet Speckle


Claret Speckle


Chestnut Speckle

| FORMAT | SIZE (mm) | THICKNESS (mm) | FINISH | COLOURS | RECOMMENDED GROUT WIDTH (mm) | BOX QTY |
|---|---|---|---|---|---|---|
| Rectangle Small Brick | 5.7 x 23.3 (+/- 0.2) | 8.5 | Glazed (Porcelain Base) | All | 3 | 38 |

**Planning & Layout** - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable tile backer board or cement board. Do not use plasterboard

**Cutting Advice** - Use a water-cooled flat-bed tile cutter with a smooth-profiled unslotted blade and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding block. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur. We do not recommend glazed tiles are used for external mitres.

**Sealing & Grouting Advice** - We recommend using our Ardex FS format grout, as this has been tested with our products and is available to purchase online. We do not recommend using dark-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax) as this can cause staining. If not using Ardex FS or FL grout, then please test your chosen grout on a sample before applying to the wall.

**Installation Notes** - Please refer to the Biblioteca installation Guide online. Please note the Speckle Brick is for wall use only. The Plain Brick can be used on the wall and floor. These tiles slightly vary in dimension and thickness, especially between batches. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase. Due to the undulating profile of these tiles, your tiler will need to take extra care when installing.

**Ongoing Maintenance** - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk