Claybrook.

BUNGALOW 22

The Beverly Hills Hotel, built in a Moorish inspired Mediterranean style was the influence behind these zellige-like tiles. Bungalow 22 is a glazed wall tile collection featuring four sizes and six colourways, each in tones that vary tile to tile.

18 BASES / 6 COLOURS / 1 FINISH / 4 FORMATS



Bungalow 22 Peach Cocktail and Pink Palace Square and Small Brick



Bungalow 22 Lawn Green Small Brick

SMALL BRICK




Moorish White



Peach Cocktail



Pink Palace



Wine Time



Pool Blue



Lawn Green

LONG BRICK



Moorish White



Peach Cocktail



Pink Palace



Wine Time



Pool Blue



Lawn Green



Shade Variation / V4 - Extreme



Requires Sealing / No



Material / Glazed Ceramic

Recycled Content / 56%

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.
If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.12.25

Claybrook.

BUNGALOW 22

Installation and Technical Advice

SQUARE


Moorish White


Peach Cocktail


Pink Palace


Wine Time


Pool Blue


Lawn Green

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle Small Brick	62 x 125	7-9	Glazed Ceramic	All	1-2	76
Rectangle Long Brick	62 x 250	7-9	Glazed Ceramic	All	1-2	31
Rectangle Slim Brick	40 x 335	7-9	Glazed Ceramic	All	1-2	40
Square	125 x 125	7-9	Glazed Ceramic	All	1-2	38

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable tile backer board or cement board. Do not use plasterboard

Cutting Advice - Use a water-cooled flat-bed tile cutter with a smooth-profiled unslotted blade and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding block. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - We recommend using our Ardex FS format grout, as this has been tested with our products and is available to purchase online. We do not recommend using dark-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax) as this can cause staining. If not using Ardex FS or FL grout, then please test your chosen grout on a sample before applying to the wall.

Installation Notes - For wall use only. These tiles slightly vary in dimension and thickness, especially between batches. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase. Due to the undulating profile of these tiles, your tiler will need to take extra care when installing. We do not recommend installing the slim brick format in a brick bond or stagger bond, as their thin linear nature will be prone to bowing.

Ongoing Maintenance - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner.

For further advice on installation please contact **enquiries@claybrookstudio.co.uk** with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk