

Claybrook.

# CORRUGATION

These Spanish made glazed wall tiles have convex, ridged and flat brick-shaped options in four lovely shades. With ribbed and tactile features, they are great at helping create architectural definition.

15 BASES / 2 FINISHES / 1 FORMAT



Corrugation White and White Ripple



Corrugation White and Blue Ripple

## COLOURS



Green



Green Pinnacle



Green Ripple



Blue



Blue Pinnacle



Blue Ripple

## COLOURS



Apricot



Apricot Pinnacle



Apricot Ripple



White



White Pinnacle



White Ripple

Print colours may vary from actual product, so tile samples should be requested before ordering.

For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact [enquiries@claybrookstudio.co.uk](mailto:enquiries@claybrookstudio.co.uk) or [technical@claybrookstudio.co.uk](mailto:technical@claybrookstudio.co.uk)



# CORRUGATION

## Installation and Technical Advice



White Matt



White Matt Pinnacle



White Matt Ripple

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	62 x 250	8.5	Glazed Ceramic	All	3	28
Rectangle - Pinnacle	62 x 250	8.5 - 12.5	Glazed Ceramic	All	3	28
Rectangle - Ripple	62 x 250	8.5 - 9.5	Glazed Ceramic	All	3	28



Shade Variation / V2 - Slight



Requires Sealing / No



Material / Glazed Ceramic

Recycled Content / 62%

**Installation Notes** - For wall use only. These tiles may vary in size, colour and tone both within batch and from batch to batch. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase, to minimise the variance. Due to the relief profile of these tiles, your tiler will need to take extra care when cleaning back the grout. When mixing profiles please note there will be a slight variation in tile size which will need to be allowed for in the 3mm grout joint.

**Planning & Layout** - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable plywood or cement board. Do not use plasterboard

**Cutting Advice** - Use a water-cooled flat-bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

**Sealing & Grouting Advice** - We recommend a 3mm grout joint to allow for any slight variation in dimensional tolerance. We also recommend you use our Ardex FS grout (for a smooth finish) or Ardex FL grout (for a grainier textured finish), as these have been tested with our products and is available to purchase through our website. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax), as these can enter the glaze and make the tiles difficult to clean-down after grouting.

**Ongoing Maintenance** - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile will need periodically re-sealing to maintain the seal (approx. once every couple of years depending on use).

For further advice on installation please contact [technical@claybrookstudio.co.uk](mailto:technical@claybrookstudio.co.uk) with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact [enquiries@claybrookstudio.co.uk](mailto:enquiries@claybrookstudio.co.uk) or [technical@claybrookstudio.co.uk](mailto:technical@claybrookstudio.co.uk)

