Claybrook.

DIJON TUMBLED LIMESTONE

Our Dijon tumbled limestone is fantastic for those seeking neutral stone tiles. Limestone has a warm and earthy hue due to its geological make-up, with tones that vary from beige-gold and taupe to lighter creams and grey-brown. Available in indoor and outdoor formats.

1 COLOUR / 1 FINISH / 6 FORMATS



Dijon Tumbled Limestone 60x40



Dijon Tumbled Limestone 60x40

COLOUR



Dijon Tumbled Limestone

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)
Rectangle	50 x 200	13	Limestone	All	3
Square	200 x 200	13	Limestone	All	3
Rectangle	200 x 400	13	Limestone	All	3
Square	400 x 400	13	Limestone	All	3
Rectangle	400 x 600	13	Limestone	All	3
Rectangle	600 x 900	13	Limestone	All	3
Outdoor - Rectangle	400 x 600	30	Limestone	All	3

Print colours may vary from actual product, so tile samples should be requested before ordering. For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

Claybrook.

DIJON TUMBLED LIMESTONE

Installation and Technical Advice



Shade Variation / V3 - Moderate



Requires Sealing / Yes



Material / Limestone

Planning & Layout - All substrates should be flat, movement-free, dust-free and primed using Ardex P51 Primer and Bonding Agent. If the tiles are being used in a shower area, then the walls must be suitably prepared with tile backer board and waterproofed with a tanking product like Ardex Waterproof Protection Kit. Whilst stone tiles can be used on wet-room floors, it is worth noting that the ongoing maintenance will need more care than with porcelain tiles. The stone will need sealing initially and then periodically deep cleaned and re-sealed. We recommend the EcoPro Tec Natural Finish Stone Sealer for sealing and the EcoPro Tec Stone & Porcelain Aftercare Cleaner for everyday cleaning and the EcoPro Tec Intensive Cleaner for the occasional deep clean.

Substrate - As per our Tile Installation Guide, we do not recommend fixing any tile directly to standard plasterboard and/or walls that have been skimmed with a thin coat of plaster. We recommend the use of tile backer board and/or a membrane system in any wet areas.

Cutting Advice – We recommend using a flat-bed water-cooled tile cutter and planning the tile layout in such a way to avoid cuts less than 15mm. Always cut through the tile with the visible face uppermost and tidy any chipping with a rubbing/sanding stone or wet and dry paper. Ensure the tile cutter blade is sharp, clean, unslotted and continuous with a smooth cutting face. Also ensure the water is regularly changed otherwise excess staining can occur.

Fixing, Sealing & Grouting Advice – With all our stone/marble tiles, it is recommended to use Ardex X7W standard set white adhesive and we recommend sealing the tiles with at least two coats of EcoProTec Natural Finish Stone Sealer before grouting with Ardex FS or Ardex FL grout. Then once the excess grout has been removed and the floor is completely dry, the installer can apply another coat across both tile and grout.

Ongoing Maintenance – We recommend using EcoPro Tec Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not attack the surface of the tile or grout. For an occasional deep clean, you can use EcoPro Tec Intensive Cleaner at the correct dilution advice on the bottle. For advice on commercial installations please see the Stone Installation guide or contact technical@claybrookstudio.co.uk with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact:
enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

Installation Notes: This type of stone features a variety of gold and grey veining which is a natural characteristic of the stone, making each tile beautifully unique

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk