

MP90 ECO XTREME



EXTREME ECO-COMPATIBLE WATER- AND OIL-REPELLENT PROTECTION

**POLISHED PORCELAIN TILES,
MARBLE AND GRANITE,
NATURAL STONE AND AGGLOMERATES,
CONCRETE**



Thanks to the innovative **ULTIMATE SHIELD TECHNOLOGY**, developed in the FILA research laboratories, the product can be applied in the presence of residual humidity, a mere 24 hours after the initial wash.



COVERAGE (1litre)

POLISHED PORCELAIN TILES	30-50 m²
MARBLE/GRANITE	20-30 m²
NATURAL STONE	10-20 m²

Coverage shown is for guidance purposes only and refers to single coats.

Packaging

- 375 ml bottles in boxes of 12.
- 1-litre cans in boxes of 6.
- 5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures.
- Ventilate the premises well during use and while the product is drying.
- Does not protect against acidic aggression.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- Water- and oil-repellent with natural effect.
- The best environmentally-friendly stain protection for porcelain tiles, natural stone, marble and granite with polished, brushed and matt honed finishes.
- Reduces absorption without affecting the material's natural look.
- It waterproofs, protects and facilitates cleaning.
- It is also ideal for grouting joints, ceramic and crackle effect surfaces, grit, resin-marble, and stone slabs.
- Is also suitable for treating coloured cement tiles and reconstructed stones.
- Scratch resistant: by protecting the surface, scratches can be removed easily during the cleaning process.
- Water- and oil-repellent: it hampers the absorption of common watery and oily stains.

ADVANTAGES

- This product has extremely low VOC emissions: certified by GEV and marked EC1plus.
- Contributes towards LEED credits.
- Hydrocarbon solvent free: environmentally-friendly treatment.
- Due to its water-base, it withstands residual humidity and can therefore be applied 24-48 hours after the initial wash, making treatment quicker.
- Single-coat application: apply and rub in gently until completely absorbed.
- Does not form surface film and does not yellow.
- It is ideally suited for protecting kitchen and bathroom tops.
- The surface can be walked on after just 2 hours*.

* Application conditions:
temperature: 20°C
humidity < or = 60%
Apply according to the
indications shown on the label.

HOW TO USE

No dilution required: ready to use.

Application: shake before use.

For materials with matt finish (natural stone, terracotta, agglomerates, cement tiles): apply **MP90 ECO XTREME** evenly and continuously on a clean and dry surface using a brush or fleece pad, wetting the grout lines as well. Dab any excess product with a clean cloth before it dries. On highly absorbent materials, apply two coats of product with a 20-minute interval in between.

For polished porcelain tiles, natural stone, agglomerates with glossy finish: apply **MP90 ECO XTREME** on a clean and dry surface, wetting the material and grout lines completely using a brush or fleece pad. Before the product dries (roughly 10-15 minutes), rub it using a microfibre cloth wetted with the product to favour its penetration. Dry the surface with a clean cloth. To speed up the process, it is possible to treat the surface with a single-disc floor scrubber.

To complete the cycle with the finish: on porous materials such as natural stone, reconstructed tiles, agglomerates and cement tiles laid in indoor environments, a finishing wax can be applied depending on the material and on the desired effect (**MATT, SATIN, CLASSIC, LONGLIFE**). The surface can be walked on after just 4 hours. The stain-proofing effect starts after 24 hours.

Maintenance: use a diluted solution of **CLEANER PRO**.

Caution:

*Before applying **MP90 ECO XTREME** to the entire surface, test the product on a small area to check for colour changes.*

Do not apply the product externally if rain is forecast.

Does not protect against acidic aggression.