



SATIN-EFFECT PROTECTIVE WAX

**TERRACOTTA, QUARRY TILES, UNPOLISHED
STONE AND AGGLOMERATES, CONCRETE TILES**



WHAT IT'S FOR

- Ideal both for treatment and maintenance.
- Protects unpolished natural stones (limestone, slate, etc.), red stoneware, non-vitrified quarry tiles and various types of terracotta.
- Recommended for treating floors made of: slate, manufactured stone and concrete tiles.
- Highly recommended for maintenance of marble and natural stone with brushed finish.

ADVANTAGES

- The product is self-polishing, but can also be polished to restore or increase shine.
- A 3-in-one solution: protects, maintains and gives floors an excellent finish.
- Original new satin look.
- Ideal to create prestigious floors: enhances the beauty of the surface.
- Easy to apply and maximum coverage.
- Does not degenerate with maintenance.



COVERAGE

With one litre:

Terracotta 30 m²

Stone 30/40 m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre: boxes of 12.

5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost. Store at room temperature.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

HOW TO USE IT

Dilution: either undiluted or diluted according to requirements. Using fleece or other applicator, apply an even coat of the product on the clean and dry floor. After one hour, apply a second coat at right angles to the first. The floor can be walked on after roughly half an hour. For improved sheen, buff the surface with a floor polisher or woollen cloth.

For maintenance:

Restoring sheen (every 2-3 months): after cleaning the surface with a diluted solution of **CLEANER PRO** (1:200), apply **SATIN** diluting 500 ml of product in 5 litres of water. For greater shine, wait till floor is dry (after about 1 hour) and buff with a wool cloth or floor polisher.

To restore the finish (once a year): apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour). apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour).

Caution:

Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).



- TERRACOTTA
- QUARRY TILES
- UNPOLISHED STONE AND AGGLOMERATES



WHAT IT'S FOR

- Protects unpolished natural stone (limestone, sandstone, slate, etc.) vitrified quarry tiles and various types of terracotta.
- Ideal both for treatment and maintenance.

ADVANTAGES

- The product is self-polishing, but can also be polished to restore or increase shine.
- A 3-in-one solution: protects, maintains and gives floors an excellent finish.
- Original new satin look.
- Ideal to create prestigious floors: enhances the beauty of the surface.
- Easy to apply and maximum coverage.
- Does not degenerate with maintenance.

COVERAGE

With one litre:

Terracotta	30 m ²
Stone	30/40 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Caution:

Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).

HOW TO USE IT

Dilution: either undiluted or diluted according to requirements.

Using a cloth or other applicator, apply an even layer of the product onto a clean dry floor surface. After one hour, apply a second coat at right-angles to the first. The floor is ready to walk on after about half-an-hour. For better sheen, buff with a floor polisher or a lint free cloth.

An initial protection coat of FILAFOB water-repellent protector is recommended on highly absorbent terracotta and stone (such as limestone, sandstone and travertine) or FILAW68.

For maintenance:

Restoring sheen (every 2-3 months): after cleaning the surface with a diluted solution of FILACLEANER (1:200), apply FILASATIN diluting 500 ml of product in 5 litres of water: For greater shine, wait till floor is dry (after about 1 hour) and buff with a wool cloth or floor polisher.

Renewing protection (once a year): apply undiluted wax with a cloth, fleece pad or other applicator. Buff the surface when it is dry (after about 1 hour).

Packaging

- 1 litre cans in boxes of 12.
- 5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost. Store at room temperature.

TEMPERATURES

Storage temperature: from 5° to 30° C
The product must be applied to material with a temperature of between 10° and 30°C.

COMPOSITION

Emulsion of synthetic wax, polymer suspensions, fragrance and appropriate additives.

LABELLING

No safety and risk labelling or instructions are required, as the product is not classified as hazardous under current regulations.

Contains: 2,2,2"-(Hexahydro-1,3,5-triethyl-1,3,5-triazine-1,3,5) triethanol.

May produce an allergic reaction.

TECHNICAL FEATURES

Appearance: liquid
Color: milky white
Odour: floral bouquet
Density: 1.010 kg/l
pH: 8.1

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.