Claybrook.

GEORGETOWN

The historic neighbourhood of Georgetown was the inspiration behind these terracotta-toned porcelain tiles. The district, situated along the Potomac river, has many homes and properties with beautiful 18th and 19th century facades in brick, produced with similarly mellow pigments.

1 COLOUR / 1 FINISH / 3 FORMATS




Georgetown Samples

COLOURS



Square



Hexagon



Brick

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	60 x 245	10	Porcelain	All	3	34
Square	250 x 250	10	Porcelain	All	3	16
Hexagon	220 x 250	10	Porcelain	All	3	25

Shade Variation / V4 - Extreme

Slip Rating / R11

Material / Porcelain

Requires Sealing / No

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.

* A ramp slip rating (R) and/or PTV Slider 96/55 value where quoted, are determined from tests carried out on one batch and the result can vary from batch to batch. Please contact technical@claybrookstudio.co.uk for further information.

1.5.24

Claybrook.

GEORGETOWN

Installation and Technical Advice

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls or joist floors, then all movement must be made absolutely minimal using suitable plywood or tile backer board. If planning to brick-bond tiles, please use tile levelling clips to minimise any bowing.

Cutting Advice – Always use a water-cooled tile cutter and plan the tile layout to avoid cuts of less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen, sharp cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - No sealer required. To avoid excessive grout residue/haze, we recommend using our Ardex FL format grout which has been tested with our products and is available to purchase online. We do not recommend using dark contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting. The application of EcoProTec Pre Grout Protector before grouting will help reduce the chance of grout haze and there is some evidence that if applied across tile surface after the installation is complete, then this helps the tiles repel organic stains, especially if the daily cleaner being used is ph neutral (like EcoProTec Aftercare).

Ongoing Maintenance – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tile's slip rating and will not attack the surface of the grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile does not need re-sealing.

For further advice on installation please contact **technical@claybrookstudio.co.uk** with any questions.

TECHNICAL DATA	INDUSTRY STANDARD	REQUIREMENT	PRODUCT VALUE
Length and Width	BS UNI ENISO 10545-2	0.6% +/- 2mm	>0.6%
Thickness	BS UNI ENISO 10545-2	5% +/- 0.5mm	≤ 5%
Edge Straightness	BS UNI ENISO 10545-2	0.5% +/- 1.5mm	>0.5%
Rectangularity	BS UNI ENISO 10545-2	0.5% +/- 2mm	>0.5%
Surface Flatness	BS UNI ENISO 10545-2	0.5% +/- 2mm	>0.5%
Surface Appearance (% of surface free of flaws)		≥95%	≥95%
Water Absorption	BS UNI ENISO 10545-3	≤0.5%	>0.5%
Breaking Strength	BS UNI ENISO 10545-4	≥35N/mm2	≥1300N/mm2
Resistance to Abrasion	BS UNI ENISO 10545-7	≥175mm3	P.E.I IV
Linear Thermal Shock Expansion	BS UNI ENISO 10545-8	No provision	
Frost Resistance	BS UNI ENISO 10545-12	No alteration to surface	Resistant
Chemical Resistance (domestic)	BS UNI ENISO 10545-13	UB min	Resistant
Stain Resistance (domestic)	BS UNI ENISO 10545-14	Declared value	Resistant

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.5.24