

Claybrook.

IDILLIO

These smart straight-edged wall tiles are designed to be jointly utilised; both square and metro style bricks tiled to create a distinctive modular configuration. In a gloss finish, they would be ideal for a bathroom, or perhaps as a practical kitchen wall or splashback.

6 BASES / 1 FINISH / 2 FORMATS



Idillio Clay rectangle and Cream square



Idillio Olive, Cream and Plaster rectangle, Olive square

COLOURS - RECTANGLES



White Gloss



Cream Gloss



Sand Gloss



Plaster Gloss




Clay Gloss



Olive Gloss

COLOURS - SQUARES



White Gloss



Cream Gloss



Sand Gloss



Plaster Gloss



Clay Gloss



Olive Gloss

Print colours may vary from actual product, so tile samples should be requested before ordering.

For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk



Claybrook.

IDILLIO

Installation and Technical Advice

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	62 x 125	8.5	Glazed Ceramic	All	2	76
Square	125 x 125	8.5	Glazed Ceramic	All	2	38



Shade Variation / V2 - Slight



Requires Sealing / No



Material / Glazed Ceramic

Recycled Content / 56%

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable plywood or cement board. Do not use plasterboard

Cutting Advice - Use a water-cooled flat-bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice – Must be sealed before grouting and ideally before even being installed. To avoid grout residue entering the crackle glaze we recommend sealing with the LTP Crackle Glaze Protector before grouting. Please use our Ardex FL format grout, which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax) , as these can enter the craze and make the tiles difficult to clean-down after grouting.

Ongoing Maintenance – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile will need periodically re-sealing to maintain the seal (approx. once every couple of years depending on use).

Installation Notes - For wall use only. These tiles may vary in colour and tone both within batch and from batch to batch. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase, to minimise the variance. To create the modular look please use 2mm grout joints.

For further advice on installation please contact technical@claybrookstudio.co.uk with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

