

CLEANING SEALING & AFTERCARE

BOILED LINSEED OIL IMPREGNATING SEALER TECHNICAL DATA SHEET

REF: 11/5/2 FEBRUARY 2021



LTP BOILED LINSEED OIL

Impregnating Oil Based Sealer.

Interior and exterior use.

Traditional sealer for terracotta and wood.

For protecting and enhancing machine and hand made terracotta. Fills and hardens within the open pores of the terracotta inhibiting the absorption of grime and fluids. Offers good mechanical strength to low fired handmade terracotta. Ideal for wooden garden furniture and decking.

IMPORTANT: Do not let the oil oxidise on the surface. Remove any unabsorbed surplus within one hour of the application using a clean cloth and, if necessary, a little White Spirit. Experiment on your surface to establish the number of coats required to achieve full saturation.

Directions for use:

Terracotta: Apply by brush a coat at a time until the tiles are saturated. Allow at least 12 hours between each coat to ensure that the oil thoroughly cures. Most Terracotta will take one or two coats to reach saturation, while others, particularly some of hand made terracotta, may take as many as four or five coats. Leave the final coat to dry for at least 24 hours before polishing with LTP Clear or Antique Wax or finishing with LTP Ironwax Gloss or Satin.

Wood: Ensure that the surface is clean and dry. Apply with a paint brush or cloth following the grain and allow to absorb and dry.

Coverage M² per coat (approx.)

| | 2ltr | 5ltr |
|--------------------------|------------------|------------------|
| Lower porosity surfaces | 30m ² | 75m ² |
| Medium porosity surfaces | 20m ² | 50m ² |
| Higher porosity surfaces | 10m ² | 25m ² |

Storage information:

Keep in a cool, dry, frost-free environment. Shelf Life – Up to 4 years for un-opened containers

Other:

Clean application brushes with white spirit.

Health, Safety & Environmental:

Keep out of the reach of children.

Do not drink. Keep away from clothing/combustible materials. Store in a closed container. May cause minor irritation on skin contact. May cause minor irritation on eye contact.

Dispose of contents/container to a licensed waste centre in accordance with local/regional /national/international regulations.

Label in Accordance With (EC) No 1272/2008

DO NOT LEAVE SOILED APPLICATION CLOTHS WHERE THEY MAY CONSTITUTE A FIRE RISK, AS THEY ARE LIABLE TO SPONTANEOUS COMBUSTION.

Important:

All rags and cloths used should be immediately burnt, or if this is not possible soaked in soapy water before disposing of in a bin. The application cloths should never be crumpled up into a ball.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

