Claybrook.

MARMORINO

This clever collection brilliantly replicates plaster finishes for a raw, earthy feel that adds both colour and a sense of texture and movement. Lovely for walls or floors, the series has five beautiful colours.

5 COLOURS / 1 FINISH / 2 FORMATS



Marmorino Manin



Marmorino Manin and Chiodo

COLOURS



Rialto



Manin



Chiodo



Paglia



Paradiso

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Square	594 x 594	9	Porcelain	All	3	4
Rectangle	594 x 1190	9	Porcelain	Manin, Chiodo, Paglia	3	3

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.

* A ramp slip rating (R) and/or PTV Slider 96/55 value where quoted, are determined from tests carried out on one batch and the result can vary from batch to batch. Please contact technical@claybrookstudio.co.uk for further information.

Claybrook.

MARMORINO

Installation and Technical Advice


Shade Variation / V3 - Moderate


Slip Rating / R10 A+B | PTV 36+ Shod


Material / Porcelain


Requires Sealing / No

Recycled Content / 41%

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls or joist floors, then all movement must be made absolutely minimal using suitable plywood or tile backer board. If planning to brick-bond tiles, please use tile levelling clips to minimise any bowing.

Cutting Advice – Always use a water-cooled tile cutter and plan the tile layout to avoid cuts of less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen, sharp cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - No sealer required. To avoid excessive grout residue, we recommend using our Ardex FL format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting.

Ongoing Maintenance – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tile's slip rating and will not attack the surface of the grout. For an occasional dee per clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile does not need re-sealing.

For further advice on installation please contact **technical@claybrookstudio.co.uk** with any questions.

TECHNICAL DATA	INDUSTRY STANDARD	REQUIREMENT	PRODUCT VALUE
Length and Width	BS UNI ENISO 10545-2	0.6% +/- 2mm	>0.2%
Thickness	BS UNI ENISO 10545-2	5% +/- 0.5mm	≤ 3%
Edge Straightness	BS UNI ENISO 10545-2	0.5% +/- 1.5mm	>0.2%
Rectangularity	BS UNI ENISO 10545-2	0.5% +/- 2mm	>0.2%
Surface Flatness	BS UNI ENISO 10545-2	0.5% +/- 2mm	>0.2%
Surface Appearance (% of surface free of flaws)		≥95%	≥95%
Water Absorption	BS UNI ENISO 10545-3	≤0.5%	>0.05%
Breaking Strength	BS UNI ENISO 10545-4	≥35N/mm2	≥40N/mm2
Resistance to Abrasion	BS UNI ENISO 10545-7	≥175mm3	>145mm3
Linear Thermal Shock Expansion	BS UNI ENISO 10545-8	No provision	a≥ 7.10(-6) Centigrade -1
Frost Resistance	BS UNI ENISO 10545-12	No alteration to surface	Resistant
Chemical Resistance (domestic)	BS UNI ENISO 10545-13	UB min	Resistant
Stain Resistance (domestic)	BS UNI ENISO 10545-14	Declared value	Resistant

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk