Claybrook.

MONTEREY

This gorgeous series is named after the famed seaside city of Monterey. Consisting of six colourways in a brick format with rustic edge, the tiles appear mottled or speckled; more apparent on the darker shades where they take on an almost tortoiseshell appearance.

6 COLOURS / 1 FINISH / 1 FORMAT



Monterey Coconut and Mustard



Monterey Toffee

COLOURS



Coconut



Grape



Seaweed



Mustard



Toffee



Chocolate

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	50 x 150	9	Glazed Ceramic	All	min 3	60

Shade Variation / V3 - Moderate

Material / Glazed Ceramic

Requires Sealing / Yes - colours Chocolate, Toffee and Mustard

Recycled Content / 43%

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.
If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.725

Claybrook.

MONTEREY

Installation and Technical Advice

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable tile backer board or cement board. Do not use plasterboard

Cutting Advice - Use a water-cooled flat-bed tile cutter with a smooth-profiled unslotted blade and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding block. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - We recommend using our Ardex FS format grout, as this has been tested with our products and is available to purchase online. We do not recommend using dark-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax) as this can cause staining. If not using Ardex FS or FL grout, then please test your chosen grout on a sample before applying to the wall. Our Chocolate, Toffe and Mustard colourways have a crackle glaze. We recommend that any crackle glaze finish tile should be sealed with LTP Crackle Glaze Tile Protector before grouting, especially important in wet areas and behind cookers. Crackle glaze tiles are not suitable for external mitres.

Installation Notes - For wall use only. These tiles slightly vary in dimension and thickness, especially between batches. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase. Due to the undulating profile of these tiles, your tiler will need to take extra care when installing.

Ongoing Maintenance - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner.

For further advice on installation please contact **enquiries@claybrookstudio.co.uk** with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk