

Claybrook.
MOULAY

After a Moroccan fact-finding trip to Moulay Yacoub, north of Fez, we were inspired by the traditional handmade Zellige tile being produced there. Although machine made, our Moulay range has all the same inherent charm with natural colour variation tile to tile.

3 BASES / 1 FINISH / 1 FORMAT




Moulay Spa



Moulay Rosewater

BASE



Pumice

Spa

Rosewater



Pumice

Spa

Rosewater

Notes: Please be aware these tiles vary greatly in shade within each colour option, and one sample will not be representative of the selection you will receive if ordering larger quantities. Please see photography for example variation.

Print colours may vary from actual product, so tile samples should be requested before ordering. For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk



Claybrook. MOULAY

Installation and Technical Advice

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Square	115 x 115	10	Glazed Ceramic	All	3 - 5	38



Shade Variation / V4 - Extreme



Requires Sealing / No



Material / Glazed Ceramic

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable plywood or cement board.

Cutting Advice - Use a water-cooled flat bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - No sealer required. To avoid excessive grout residue, we recommend using our Ardex FS format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting.

Ongoing Maintenance - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile does not need re-sealing.

Installation Notes - For wall use only. Tiles may vary in colour from batch to batch. This is for colour reference only. Please be aware these tiles vary greatly in shade within each colour option, and one sample will not be representative of the selection you will receive if ordering larger quantities.

For further advice on installation please contact technical@claybrookstudio.co.uk with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

