

Claybrook.

NETTUNO

Named after the Fountain of Neptune in our favourite square in Bologna, these Italian made wall tiles have a beautiful combination of colour and glaze. The six available shades, each giving a soft watery visual effect, are in options ideal for bathrooms and kitchens.

6 BASES / 1 FINISH / 1 FORMAT



Nettuno Latte



Nettuno Parkland


VARIATION



Dove




Fountain



Latte



Sand



Parkland



Ripple

COLOURS



Dove



Fountain



Latte



Sand



Parkland



Ripple

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	60 x 250	9.5	Glazed Porcelain	All	3	32

Print colours may vary from actual product, so tile samples should be requested before ordering.

For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk



Claybrook.

NETTUNO

Installation and Technical Advice



Shade Variation / V4 - Extreme



Requires Sealing / No



Material / Glazed Porcelain

Planning & Layout - all substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable plywood or cement board.

Cutting Advice - use a water-cooled flat bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - no sealer required. To avoid excessive grout residue, we recommend using our Ardex FS format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting.

Ongoing Maintenance - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile does not need re-sealing.

Installation Notes - For wall use only. Tiles may vary in colour from batch to batch. This is for colour reference only. Please be aware these tiles vary greatly in shade within each colour option, and one sample will not be representative of the selection you will receive if ordering larger quantities. These tiles have a gloss finish, though in order to emulate a more rustic appearance, some edges can have a matt appearance.

For further advice on installation please contact technical@claybrookstudio.co.uk with any questions.

TECHNICAL DATA	INDUSTRY STANDARD	REQUIREMENT	PRODUCT VALUE
Water Absorption	BS UNI ENISO 10545-3	≤0.5%	>0.5%
Breaking Strength	BS UNI ENISO 10545-4	≥30N/mm ²	>35N/mm ²
Crazing resistance	BS UNI ENISO 10545-4		Resistant
Chemical Resistance (domestic)	BS UNI ENISO 10545-13	GB min	GA
Stain Resistance (domestic)	BS UNI ENISO 10545-14	Declared value	Class 5

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

