

Claybrook.

OSAKA

These most elegant and pretty matt finish tiles and decors have a hint of Japanese simplicity and a soft crackle finish. The exuberant chrysanthemum pattern is particularly striking.

3 COLOURS / 1 FINISH / 2 FORMATS / 2 FINISHING PIECES / 2 DECORS



Osaka Kita 7.5x30 and Decor 1



Osaka Kita 7.5x30 and Decor 1

COLOURS



Kita

Minami

Semba

DECORS



Decor 1

Decor 2

FORMATS



Rectangle 7.5x15

Rectangle 7.5x30

Dado

Skirting

FINISHING PIECES



Shade Variation / V2 - Slight



Requires Sealing / Yes - See notes on sealing advice



Material / Crackle Glazed Ceramic

Print colours may vary from actual product, so tile samples should be requested before ordering.

For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk



Claybrook.

OSAKA

Installation and Technical Advice

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	75 x 150	9	Crackle Glazed Ceramic	All	3 - 5	80
Rectangle	75 x 300	9	Crackle Glazed Ceramic	All	3 - 5	50
Dado	60 x 300	26	Crackle Glazed Ceramic	All	3 - 5	22
Skirting	130 x 300	13	Crackle Glazed Ceramic	All	3 - 5	16
Decor 1	150 x150	9	Crackle Glazed Ceramic	All	3 - 5	35
Decor 2	150 x150	9	Crackle Glazed Ceramic	All	3 - 5	35

Planning & Layout - all substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls or joist floors, then all lateral movement must be made absolutely minimal using suitable plywood or cement board. The colour, tone and crazing of these tiles can vary between batches, so where possible try to order sufficient product to complete your project, even if it means storing the tiles on site until required.

Cutting advice - use a water-cooled flat-bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise dirty water can stain the crazing and excess chipping can occur.

Sealing advice - These tiles require sealing with at least two coats of LTP Crackle Glaze Protector before grouting. We also suggest applying a single coat after the grout joint has completely dried, as this will help with water repellency and ongoing cleaning. We only recommend using Ardex FL grouts and Ardex Standard Set White adhesive and **do not recommend the use of black or dark coloured grouts with a crackle glazed tile, especially with white or lighter coloured tiles.** With any crackle glaze tile, dark grouts can leave a residue in the crazing that is impossible to remove. If not using our recommend products then tiles should be tested with the products you are planning on using before installation.

For further advice on installation please contact technical@claybrookstudio.co.uk with any questions.

Installation Notes: For wall use only.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

