Claybrook.

PAMPHILI

Inspired by the truly beautiful Doria Pamphili Gallery, this porcelain wall tile replicates natural material. The distinctive veining is rather like Calacatta Viola or Violetta marble, in shades of dark burgundy set against a white background.

2 COLOURS / 1 FINISH / 1 FORMAT



Pamphili Salon



Pamphili Salon

COLOURS

Diana



Salon

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	150 x 450	10	Porcelain	All	3	16

Shade Variation / V3 - Moderate (Salon)
V1 - Uniform (Diana)

Material / Porcelain

Requires Sealing / No

Recycled Content / 50%

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.7.24

Claybrook.

PAMPHILI

Installation and Technical Advice

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls or joist floors, then all movement must be made absolutely minimal using suitable tile backer board.

Cutting Advice – Always use a water-cooled tile cutter and plan the tile layout to avoid cuts of less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen, sharp cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - No sealer required. To avoid grout residue/haze, we recommend using our Ardex FL/FS format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting. The application of EcoProTec Pre-Grout Protector before grouting and the use of EcoProTec Cement Residue Remover will significantly reduce the chance of grout haze.

Ongoing Maintenance – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tile's slip rating and will not attack the surface of the grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner.

Please note these tiles are unrectified so sizes will vary between colours and batches.

For further advice on installation please contact **technical@claybrookstudio.co.uk** with any questions.

TECHNICAL DATA	INDUSTRY STANDARD	REQUIREMENT	PRODUCT VALUE
Length and Width	BS UNI ENISO 10545-2	0.6% +/- 2mm	>0.6%
Thickness	BS UNI ENISO 10545-2	5% +/- 0.5mm	≤ 5%
Edge Straightness	BS UNI ENISO 10545-2	0.5% +/- 1.5mm	>0.5%
Rectangularity	BS UNI ENISO 10545-2	0.5% +/- 2mm	>0.5%
Surface Flatness	BS UNI ENISO 10545-2	0.5% +/- 2mm	>0.5%
Surface Appearance (% of surface free of flaws)		≥95%	≥95%
Water Absorption	BS UNI ENISO 10545-3	≤0.5%	>0.5%
Breaking Strength	BS UNI ENISO 10545-4	≥35N/mm2	Compliant
Resistance to Abrasion	BS UNI ENISO 10545-7	≥175mm3	Compliant
Linear Thermal Shock Expansion	BS UNI ENISO 10545-8	No provision	Resistant
Frost Resistance	BS UNI ENISO 10545-12	No alteration to surface	Resistant
Chemical Resistance (domestic)	BS UNI ENISO 10545-13	UB min	GLA/GHA
Stain Resistance (domestic)	BS UNI ENISO 10545-14	Declared value	Class 5

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk