Claybrook.

POTTERS GLAZE

In a sophisticated brick and square with just adorable colourways, these wall tiles have a sense of artisan craftsmanship that is ideal for how we live today. Informal but classic, they are brilliant contrasted with other subtle tones.

7 COLOURS / 1 FINISH / 3 FORMATS



Potters Glaze Leach



Potters Glaze Gadsby

COLOURS



Gadsby



Leach



Perry

Hepworth



Cliff



Keeling



Gadsby Square



Leach Square



Perry Square

Hepworth Square

Rie



Gadsby Metro



Leach Metro



Perry Metro

Hepworth Metro

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	75 x 150	9	Glazed Ceramic	All	3 - 5	50
Square	132 x 132	9	Glazed Ceramic	All	3 - 5	30
Rectangle	64 x 132	9	Glazed Ceramic	All	3 - 5	60

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.10.24

Claybrook.

POTTERS GLAZE

Installation and Technical Advice



Shade Variation / V2 - Slight



Requires Sealing / See Sealing and Grouting advice notes below



Material / Glazed Ceramic

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable plywood or cement board.

Cutting Advice - Use a water-cooled flat bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - No sealer required unless the tiles are being installed in a wet area such as a shower or bath surround. To avoid excessive grout residue, we recommend using our Ardex FS format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting.

Ongoing Maintenance – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile does not need re-sealing.

Installation Notes - For wall use only. Tiles may vary in colour from batch to batch. This is for colour reference only. Please be aware these tiles do vary in shade within each colour option, and one sample will not be representative of the selection you will receive if ordering larger quantities.

For further advice on installation please contact **technical@claybrookstudio.co.uk** with any questions.

TECHNICAL DATA	INDUSTRY STANDARD	REQUIREMENT	PRODUCT VALUE
Crazing resistance	BS UNI ENISO 10545-4		Resistant
Chemical Resistance (domestic)	BS UNI ENISO 10545-13	GB min	GB
Stain Resistance (domestic)	BS UNI ENISO 10545-14	Class 3 min	Class 3

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk