Claybrook.

# PRECINCT 14

The glazed wall tiles are available in seven colours that span the decorating feel of the 70' and 80's, and have an attractively aged quality with variation in tone. The brick shape is ideal for herringbone, linear designs, and could be used to create striped effects when paired together.

**7 COLOURS / 1 FINISH / 1 FORMAT**



Precinct 14 Colman



Precinct 14 Laguardia

## COLOURS



Colman



Samuels



Cagney



Lacey



Isbecki



Laguardia



Locker Room

| FORMAT | SIZE (mm) | THICKNESS (mm) | FINISH | COLOURS | RECOMMENDED GROUT WIDTH (mm) | BOX QTY |
|---|---|---|---|---|---|---|
| Rectangle | 64 x 223 | 8.5 | Glazed Ceramic | All | 3 | 48 |

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.
If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.5.26

Claybrook.

# PRECINCT 14

## Installation and Technical Advice



Shade Variation / V4 - Extreme



Requires Sealing / No



Material / Glazed Ceramic

Recycled Content / 39%

**Planning & Layout** - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable tile backer board or cement board. Do not use plasterboard

**Cutting Advice** - Use a water-cooled flat-bed tile cutter with a smooth-profiled unslotted blade and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding block. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

**Sealing & Grouting Advice** - We recommend using our Ardex FS format grout, as this has been tested with our products and is available to purchase online. We do not recommend using dark-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax) as this can cause staining. If not using Ardex FS or FL grout, then please test your chosen grout on a sample before applying to the wall.

**Installation Notes** - For wall use only. These tiles slightly vary in dimension and thickness, especially between batches. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase. Due to the undulating profile of these tiles, your tiler will need to take extra care when installing.

**Ongoing Maintenance** - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner.

For further advice on installation please contact **enquiries@claybrookstudio.co.uk** with any questions.

| TECHNICAL DATA | INDUSTRY STANDARD | REQUIREMENT | PRODUCT VALUE |
|---|---|---|---|
| Length and Width | BS UNI ENISO 10545-2 | 0.6% +/- 2mm | ≤0.6% |
| Thickness | BS UNI ENISO 10545-2 | 5% +/- 0.5mm | ≤5% |
| Edge Straightness | BS UNI ENISO 10545-2 | 0.5% +/- 1.5mm | ≤0.5% |
| Rectangularity | BS UNI ENISO 10545-2 | 0.5% +/- 2mm | ≤0.5% |
| Surface Flatness | BS UNI ENISO 10545-2 | 0.5% +/- 2mm | ≤0.5% |
| Surface Appearance (% of surface free of flaws) | | ≥95% | >95% |
| Water Absorption | BS UNI ENISO 10545-3 | ≤0.5% | <0.5% |
| Breaking Strength | BS UNI ENISO 10545-4 | ≥35N/mm2 | ≥30N/mm2 |
| Resistance to Abrasion | BS UNI ENISO 10545-6 | ≤175mm3 | > 1100 N |
| Thermal Shock Resistance | BS UNI ENISO 10545-9 | Pass | Pass |
| Frost Resistance | BS UNI ENISO 10545-12 | No alteration to surface | No alteration |
| Chemical Resistance (domestic) | BS UNI ENISO 10545-13 | GB min | LA A |
| Stain Resistance (domestic) | BS UNI ENISO 10545-14 | Class 3 min | Class 5 |