Claybrook.

SPRING HAVEN

This stunning Calacatta marble tile series has a base colour of off-white with flash-tones of peach, taupe and greige. Available in two kit-kat style mosaics. Distinctive and durable, the pretty tiles are all suitable for walls or floors.

1 COLOUR / 1 FINISH / 2 MOSAICS



Spring Haven Small and Large Kitkat mosaics

MOSAICS



Small Kitkat Mosaic



Large Kitkat Mosaic

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Small Kitkat Mosaic	298 x 304	10	Marble	All	2	10
Large Kitkat Mosaic	292 x 298	10	Marble	All	2	10

Shade Variation / V3 - Moderate

Requires Sealing / Yes

Material / Marble

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.11.24

Claybrook.

SPRING HAVEN

Installation and Technical Advice

Planning & Layout - All substrates should be flat, movement-free, dust-free and primed using Ardex P51 Primer and Bonding Agent. We do not recommend marble tiles for wet-room floors, however they can be used on shower walls if the substrate is suitably tanked and any movement is made absolutely minimal. We do not recommend fixing any tile directly to standard plasterboard and/or walls that have been skimmed with a thin coat of plaster. We recommend the use of tile backer board and/or a membrane system in any wet areas.

Cutting Advice – We recommend using a flat-bed water-cooled tile cutter and planning the tile layout in such a way to avoid cuts less than 15mm. Always cut through the tile with the visible face uppermost and tidy any chipping with a rubbing/sanding stone or wet and dry paper. Ensure the tile cutter blade is sharp, clean, unslotted and continuous with a smooth cutting face. Also ensure the water is regularly changed otherwise excess staining can occur.

Sealing & Grouting Advice – For full details on sealing and grouting, please ask your installer to read the Marble Installation Guide. With natural marble tiles, it is recommended to use Ardex X7W standard set white adhesive, as grey coloured adhesive/grout can 'dull' the marble's natural translucence. For most projects we recommend sealing the tiles with 2 coats of EcoProTec Natural Finish Stone Sealer before grouting with Ardex FS or Ardex FL grout, then applying another coat once the grout has been cleaned off and the floor is completely dry. For a more intense colour effect without the use of a finishing wax, EcoProTec Colour Enhancing Stone Sealer can be used in place of the Natural Finish Stone sealer.

Ongoing Maintenance – We recommend using EcoProTec Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not attack the surface of the tile or grout. For an occasional deep clean, you can use EcoProTec Intensive Cleaner at the dilution advice on the bottle. For advice on commercial installations please see the Installation guide or contact technical@claybrookstudio.co.uk with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

Installation Notes: Spring Haven marble features a base colour of off-white with flash-tones of peach, taupe and greige. This is a natural characteristic of the stone, making each tile beautifully unique.

TECHNICAL DATA	INDUSTRY STANDARD	REQUIREMENT	PRODUCT VALUE
Length and Width	BS UNI ENISO 10545-2	0.5% +/- 2mm	0.15%
Thickness	BS UNI ENISO 10545-2	10% +/- 0.5mm	5%
Edge Straightness	BS UNI ENISO 10545-2	0.3% +/- 1.5mm	0.1%
Rectangularity	BS UNI ENISO 10545-2	0.5% +/- 2mm	0.2%
Surface Flatness	BS UNI ENISO 10545-2	0.5% +/- 2mm	0.35%

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk