Claybrook.

# SUNSET STRIP

Inspired by the Sunset Strip in West Hollywood, this eye-catching collection is available in seven muted matt finish colour varieties for the wall, the porcelain stoneware series is ideal for domestic or commercial settings.

**7 COLOURS / 1 FINISH / 1 FORMAT**



Sunset Strip Mondrian



Sunset Strip Pink Taco

## COLOURS



Mondrian



Roxy



Marmont



Pink Taco



Rainbow



Viper



Skybar

| FORMAT | SIZE (mm) | THICKNESS (mm) | FINISH | COLOURS | RECOMMENDED GROUT WIDTH (mm) | BOX QTY |
|---|---|---|---|---|---|---|
| Rectangle | 70 x 280 (+-2) | 10 | Glazed Porcelain base | All | 3 | 24 |

* A ramp slip rating (R) and/or PTV Slider 96/55 value where quoted, are determined from tests carried out on one batch and the result can vary from batch to batch. Please contact technical@claybrookstudio.co.uk for further information.

Claybrook.

# SUNSET STRIP

## Installation and Technical Advice

 Shade Variation / V2 - Slight

 Slip Rating / R10

 Material / Glazed Porcelain base

 Requires Sealing / No

Recycled Contents / 39%

**Planning & Layout** - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls or joist floors, then all movement must be made absolutely minimal using suitable tile backer board. Sizes vary between batches and colours. If planning to install a mixer of colours or tiles purchased at separate times, please ensure that your tiler is aware so that they can install by eye and not by spacers.

**Cutting Advice** – Always use a water-cooled tile cutter and plan the tile layout to avoid cuts of less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen, sharp cutting edge, otherwise excess chipping will occur.

**Sealing & Grouting Advice** - No sealer required. To avoid grout residue/haze, we recommend using our Ardex FL/FS format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting. The application of EcoProTec Pre-Grout Protector before grouting and the use of EcoProTec Cement Residue Remover will significantly reduce the chance of grout haze.

**Ongoing Maintenance** – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tile's slip rating and will not attack the surface of the grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner.

| TECHNICAL DATA | INDUSTRY STANDARD | REQUIREMENT | PRODUCT VALUE |
|---|---|---|---|
| Length and Width | BS UNI ENISO 10545-2 | 0.6% +/- 2mm | ≤0.6% |
| Thickness | BS UNI ENISO 10545-2 | 5% +/- 0.5mm | ≤0.5% |
| Edge Straightness | BS UNI ENISO 10545-2 | 0.5% +/- 1.5mm | ≤0.5% |
| Rectangularity | BS UNI ENISO 10545-2 | 0.5% +/- 2mm | ≤0.5% |
| Surface Flatness | BS UNI ENISO 10545-2 | 0.5% +/- 2mm | ≤0.5% |
| Water Absorption | BS UNI ENISO 10545-3 | ≤0.5% | <0.5% |
| Thermal Shock Resistance | BS UNI ENISO 10545-9 | Pass | Pass |
| Frost Resistance | BS UNI ENISO 10545-12 | No alteration to surface | No alteration |
| Chemical Resistance (domestic) | BS UNI ENISO 10545-13 | GB min | GLA - GHB |
| Stain Resistance (domestic) | BS UNI ENISO 10545-14 | Class 3 min | Conforms |

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk