

# Claybrook.

## TAN-TAN

Named after the Moroccan city of Tan-Tan, these glazed porcelain tiles create a Zellige style effect for walls, reminiscent of traditional square tiling seen throughout Morocco. In a series of colours, ideal for adding depth and durability to your bathroom or kitchen refurbishment.

8 BASES / 1 FINISH / 1 FORMAT



Tan-Tan colours

### VARIATION



Couscous

Desert

Chickpea

Husk

Brick

Spice

### COLOURS



Couscous

Desert

Chickpea

Husk

Brick

Spice

Print colours may vary from actual product, so tile samples should be requested before ordering.

For advice on shade variation of V3 and above, please speak to our showroom.

If you require any further assistance regarding specification data, technical advice or samples, please contact [enquiries@claybrookstudio.co.uk](mailto:enquiries@claybrookstudio.co.uk) or [technical@claybrookstudio.co.uk](mailto:technical@claybrookstudio.co.uk)



# Claybrook.

## TAN-TAN

### Installation and Technical Advice



Adobe

Abode

Kaftan

Kaftan

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Square	100 x 100	9	Glazed Ceramic	All	3-5	51



Shade Variation / V2 - Slight



Requires Sealing / No



Material / Glazed Ceramic

Recycled Content / 42%

**Planning & Layout** - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable plywood or cement board. Do not use plasterboard.

**Cutting Advice** - Use a water-cooled flat-bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

**Sealing & Grouting Advice** – We recommend a 3mm grout joint to allow for any slight variation in dimensional tolerance. We also recommend you use our Ardex FS grout (for a smooth finish) or Ardex FL grout (for a grainier textured finish), as these have been tested with our products and is available to purchase through our website. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax), as these can enter the glaze and make the tiles difficult to clean-down after grouting.

**Ongoing Maintenance** – We recommend using EcoProtec’s Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec’s Stone and Tile Intensive Cleaner.

**Installation Notes** - For wall use only. These tiles may vary in colour and tone both within batch and from batch to batch. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase, to minimise the variance.

For further advice on installation please contact [technical@claybrookstudio.co.uk](mailto:technical@claybrookstudio.co.uk) with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact [enquiries@claybrookstudio.co.uk](mailto:enquiries@claybrookstudio.co.uk) or [technical@claybrookstudio.co.uk](mailto:technical@claybrookstudio.co.uk)

