Claybrook.

TOLENTINO

We worked directly with an Italian family atelier to get this wonderful series of real Terrazzo just right in terms of colour and production, with a traditional feel that includes some minimal pitting to the surface, that is simply filled during grouting.

1 FINISH / 1 FORMAT / 6 DECORS




Tolentino Collina




Tolentino Lucia


DECORS




Lucia




Collina




Casone



Salcito



Rotondo



Martino

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	DECORS	RECOMMENDED GROUT WIDTH (mm)
Square	400 x 400 (1-2 mm tolerance)	20	Terrazzo	All	3

Shade Variation / V3 - Moderate

Requires Sealing / Yes

Material / Terrazzo

Recycled Content / approx. 50%

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.

Claybrook.

TOLENTINO

Installation and Technical Advice

Please refer to our Terrazzo Installation Guide for details on how best to install this product.

Planning & Layout - All substrates should be flat, sound, dust-free and primed using Ardex P51 Primer and Bonding agent. We do not recommend these tiles are used for walls, as they are 20mm thick and weigh approx 8kg each. If being used for a decorative upstand (do not use behind cookers or kitchen sinks) your installer will need to factor in the weight when deciding on a fixing process.

Cutting Advice – We recommend using a flat-bed water-cooled tile cutter and planning the tile layout in such a way to avoid cuts less than 15mm. Always cut through the tile with the visible face uppermost and tidy any chipping with a rubbing/sanding stone or wet and dry paper. Ensure the tile cutter blade is clean, unslotted and continuous with a smooth cutting face. Also ensure the water is regularly changed otherwise excess staining can occur.

Sealing & Grouting Advice – For full details on sealing and grouting, please ask your installer to read the Terrazzo Installation Guide.

Ongoing Maintenance – We recommend using EcoProTec Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not attack the surface of the tile or grout. For an occasional deep clean, you can use EcoProTec Intensive Cleaner at the dilution advice on the bottle. Depending on whether EcoProTec Satin Surface Wax has been applied, and the footfall and cleaning regime, the average domestic bathroom/kitchen will need the finishing wax re-applied every 6/12 months.

For advice on commercial installations please see the Installation guide or contact technical@claybrookstudio.co.uk with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk