Claybrook.

TUTTI FLUTTI

These Italian-designed tiles have a fabulously fluted surface design, perfect for creating walls with a fluid sculptural feel in both matt and gloss options. Great used alone or paired together for striped or chequer effects. The tiles also contain over 50% recycled content.

11 BASES / 2 FINISHES / 1 FORMAT



Tutti Flutti Samples



Tutti Flutti Apple, Gooseberry and Coconut Gloss

COLOURS - GLOSS



Apple Gloss



Gooseberry Gloss




Cherry Gloss



Apricot Gloss



Peach Gloss




Coconut Gloss

COLOURS - MATT




Apple Matt



Gooseberry Matt



Cherry Matt



Apricot Matt



Peach Matt

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.
If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

1.9.24

Claybrook.

TUTTI FLUTTI

Installation and Technical Advice



Shade Variation / V2 - Slight



Requires Sealing / Yes



Material / Glazed Ceramic

Recycled Content / 56%

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Rectangle	100 x 300 (+/- 1mm)	9-11mm	Glazed Ceramic	All	2	18

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable tile backer board or cement board. Do not use plasterboard

Cutting Advice - Use a water-cooled flat-bed tile cutter with a smooth-profiled unslotted blade and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding block. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - To avoid grout residue bonding to the matt glaze we recommend applying EcoProTec Pre Grout Protector before grouting and then using EcoProTec Cement Residue Remover to remove any fine haze. We also recommend using our Ardex FS format grout, as this has been tested with our products and is available to purchase online. We do not recommend using dark-coloured or fine grouts for joint widths down to 1mm (such as Bal MicroMax) as the matt surface can trap the very fine grains and cause staining. If not using Ardex FS or FL grout, then please test your chosen grout on a sample before applying to the wall.

Installation Notes - For wall use only. These tiles slightly vary in dimension and score alignment, especially between batches. If conducting your project in phases, you will ideally need to buy all the tiles required in one purchase, to minimise the variance. Due to the relief profile of these tiles, your tiler will need to take extra care when cleaning back the grout. The relief tiles are hollow-backed, so please ensure the edges are in full contact with the adhesive to ensure a good bond. Apply the Pre Grout Protector at least one hour before grouting ensuring the protector saturates the scored lines in the surface. If using spacers, do not push the spacer to the back of the tiles as it is slightly wider at the back of the tile.

Ongoing Maintenance - We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this is a ph neutral cleaner and will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner.

For further advice on installation please contact **technical@claybrookstudio.co.uk** with any questions.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk