

Claybrook.

VILLA TERRACOTTA

Handmade in Valencia, our Villa Terracotta tiles are reminiscent of the tiles seen on floors and as roof tile throughout the ancient roman empire. The clay varies from soft yellows through to pinkish red with markings consistent with tiles overlapping within the kiln.

1 COLOUR / 1 FINISH / 7 FORMATS



Villa Terracotta samples



Villa Terracotta samples

COLOURS



Shade Variation / V3 - Moderate



Requires Sealing / Yes



Material / Terracotta

Print colours may vary from actual product, so tile samples should be requested before ordering. For advice on shade variation of V3 and above, please speak to our showroom. If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk



Claybrook.
VILLA TERRACOTTA

Installation and Technical Advice

| FORMAT | SIZE (mm) | THICKNESS (mm) | FINISH | COLOURS | RECOMMENDED GROUT WIDTH (mm) |
|-----------|-----------|----------------|------------|---------|------------------------------|
| Rectangle | 50 x 270 | 16 | Terracotta | All | 6-9 |
| Rectangle | 75 x 300 | 20 | Terracotta | All | 6-9 |
| Rectangle | 125 x 250 | 20 | Terracotta | All | 6-9 |
| Square | 150 x 150 | 16 | Terracotta | All | 6-9 |
| Rectangle | 150 x 300 | 22 | Terracotta | All | 6-9 |
| Square | 200 x 200 | 20 | Terracotta | All | 6-9 |
| Hexagon | 200 x 200 | 20 | Terracotta | All | 6-9 |

Planning & Layout – The substrate that the tiles will be adhered to must be flat, stable and dust free. If the tiles are being fixed to stud walls or joist floors, then all movement must be made absolute minimal, using the appropriate plywood or tile backer board. The substrate in shower areas also needs to be suitably waterproofed to prevent water leaking into the fabric of the building. See our Installation Guide for advice on how different substrates need to be prepared.

Cutting Advice - Villa tiles are not suitable for external mitres as the exposed edges will be both fragile and sharp. Plan the tile layout to avoid cuts less than 15mm where possible. For required cuts use a water-cooled flat-bed tile cutter and always cut through the tile with the visible face uppermost. Ensure the tile blade is clean, smooth-profiled, un-slotted and kept sharp, otherwise excess chipping will occur.. Any slight chipping can be sanded away with a rubbing/sanding stone, tile file or wet and dry sanding block. Be sure to regularly change the wate, to avoid staining the tiles.

Sealing Advice - Samples will be sent unsealed. For fixing, sealing and cleaning advice see the Terracotta Installation Guide. We recommend using Ardex Microtec adhesive and the Ardex FL format grout we sell. If you are not planning to use our recommended products, then please test your preferred products with the tiles before installation.

Installation Notes: Requires sealing. Please refer to the Claybrook Terracotta Installation Guide for installation and sealing process. We strongly recommend an experienced terracotta fitter is employed.

Tiles should be unpacked and dry laid prior to installation to ensure any natural variation is evenly distributed across the floor or wall. Sizes cannot be mixed together due to the varying thickness

If in doubt, please contact technical@claybrookstudio.co.uk with any questions prior to installation, as installed product will be deemed as accepted.

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

