Claybrook.

WESTCHESTER

These finely textured neutral-toned porcelain tiles are ideal for creating an indoor to outdoor kitchen and living space. The three colourways, each of which replicates natural stone, all have both 1cm and 2cm options to create a seamless feel when used together.

3 COLOURS / 2 FINISHES / 2 FORMATS



Westchester Hartsdale



Westchester Elmsford

COLOURS



Hartsdale



Elmsford



Larchmont

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Square	600 x 600	9	Porcelain - Rectified	All	3	4
Outdoor	600 x 1200	20	Porcelain - Rectified	All	3	1

* A ramp slip rating (R) and/or PTV Slider 96/55 value where quoted, are determined from tests carried out on one batch and the result can vary from batch to batch. Please contact technical@claybrookstudio.co.uk for further information.

Claybrook.

WESTCHESTER

Installation and Technical Advice



Shade Variation / V2 - Slight



Slip Rating / R10 A+B | PTV 36+Shod (Natural finish)
R11 A+B+C | PTV 36+ Bare (Grip finish)



Material / Porcelain



Requires Sealing / No

Recycled Content / 40%

Planning & Layout - All substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls or joist floors, then all movement must be made absolutely minimal using suitable plywood or tile backer board. Avoid brick-bonding the Allaperto 120x60 with a 1/2 overlap, instead opt for a 1/3 overlap to avoid any lipping.

Cutting Advice – Always use a water-cooled tile cutter and plan the tile layout to avoid cuts of less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen, sharp cutting edge, otherwise excess chipping will occur.

Sealing & Grouting Advice - No sealer required. To avoid excessive grout residue, we recommend using our Ardex FL format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting.

Ongoing Maintenance – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tile's slip rating and will not attack the surface of the grout. For an occasional dee per clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile does not need re-sealing.

TECHNICAL DATA	INDUSTRY STANDARD	PRODUCT VALUE (R10)	PRODUCT VALUE (R11)
Length and Width	BS UNI ENISO 10545-2	>0.5%	>0.5%
Thickness	BS UNI ENISO 10545-2	≤5%	≤5%
Edge Straightness	BS UNI ENISO 10545-2	>0.5%	>0.5%
Rectangularity	BS UNI ENISO 10545-2	>0.5%	>0.5%
Surface Flatness	BS UNI ENISO 10545-2	>0.5%	>0.5%
Surface Appearance (% of surface free of flaws)		>95%	>95%
Water Absorption	BS UNI ENISO 10545-3	>0.05%	>0.05%
Breaking Strength	BS UNI ENISO 10545-4	≥50mm3	≥50mm3
Resistance to Abrasion	BS UNI ENISO 10545-7	>145mm3	>145mm3
Thermal Shock Resistance	BS UNI ENISO 10545-9	Pass	Pass
Frost Resistance	BS UNI ENISO 10545-12	No alteration	No alteration
Chemical Resistance (domestic)	BS UNI ENISO 10545-13	A	A
Stain Resistance (domestic)	BS UNI ENISO 10545-14	Class 5	Class 5

If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk