Claybrook.


ZEZE

There is something so eye-catching and beautiful in the colours and shapes of these porcelain wall mosaics. Influenced by traditional Japanese glazing techniques, the linear tiles are available in five fantastic shade options for a modern twist on classic style.

5 MOSAICS / 1 FINISH / 1 FORMATS



Zeze Blossom Mosaic




Zeze Blossom, Orchid, Sora and Kaiyo Mosaic


COLOURS



Orchid



Blossom



Bonsai



Kaiyo



Sora

FORMAT	SIZE (mm)	THICKNESS (mm)	FINISH	COLOURS	RECOMMENDED GROUT WIDTH (mm)	BOX QTY
Mosaic	282 x 294	7	Glazed Porcelain	All	2	10

Shade Variation / V2 - Slight

Requires Sealing / No

Material / Glazed Porcelain

Print colours may vary from actual product, so tile samples should be requested before ordering.
For advice on shade variation of V3 and above, please speak to our showroom.
If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

11.21

Claybrook.

ZEZE

Installation and Technical Advice

Planning & Layout - all substrates should be flat, sound and dust free. All wet areas need to be suitably tanked and if the tiles are being fixed to stud walls, then all movement must be made absolutely minimal using suitable plywood or cement board.


Cutting advice - use a water-cooled flat bed tile cutter and plan the tile layout to avoid cuts less than 15mm where possible. Always cut through the tile with the visible face uppermost and tidy any slight chipping with a rubbing/sanding stone. Ensure the blade is kept clean with a keen cutting edge, otherwise excess chipping will occur.

Sealing & Grouting advice - no sealer required, however the application of EcoProtec Porcelain Tile Protector will assist with the removal of grout residue when installing the **matt finish**. To avoid excessive grout residue, we recommend using our Ardex FS format grout which has been tested with our products and is available to purchase online. We do not recommend using contrasting-coloured or fine grouts for joint widths down to 1mm, as these can cling to the surface making the tiles more difficult to clean-down after grouting.

Ongoing Maintenance – We recommend using EcoProtec's Stone and Porcelain Aftercare Cleaner for daily cleaning purposes, as this will not affect the tiles surface or grout. For an occasional deeper clean, you can use EcoProtec's Stone and Tile Intensive Cleaner. The tile does not need re-sealing.

Installation Notes - For wall use only. Tiles may vary in shade from batch to batch. These mosaics are set on a mesh backing.

For further advice on installation please contact **technical@claybrookstudio.co.uk** with any questions.



If you require any further assistance regarding specification data, technical advice or samples, please contact enquiries@claybrookstudio.co.uk or technical@claybrookstudio.co.uk

11.21